



产品说明

BAEROSTAB UBZ 293 TR

描述	类型	钡锌稳定剂
Description	Type	BaZn stabiliser
	外观	液体
	Appearance	liquid

性能/应用 BAEROSTAB UBZ 293 TR 是高效的钡锌稳定剂，适合加工半硬和软质，透明和有色的压延薄膜和片材。

Performance / Application BAEROSTAB UBZ 293 TR is an efficient BaZn stabiliser for the manufacture of semi-rigid and flexible, transparent and pigmented calendered film and sheeting.

BAEROSTAB UBZ 293 TR 能确保良好的动态和静态热稳定性，较好的光稳定性，较佳的初始颜色，以及加工无析出性能。

BAEROSTAB UBZ 293 TR ensures good dynamic and static thermostability, good light resistance, good initial colour and plate-out-free processing.

用BAEROSTAB UBZ 293 TR加工的薄膜和片材具有优异的印刷性能和焊接性能。BAEROSTAB UBZ 293 TR 有优秀的抗硫污性能。

Film and sheeting stabilised with BAEROSTAB UBZ 293 TR exhibit very good printability and weldability. BAEROSTAB UBZ 293 TR displays excellent sulphide stain resistance.

推荐用量: 2.0 - 4.0 phr。

Dosage range: 2.0 - 4.0 phr.

与环氧增塑剂如环氧大豆油配合使用，可进一步提高产品的热稳定性和光稳定性。

A combination with epoxy plasticiser like ESBO improves heat and light stability further.

本产品的材料安全数据表可应客户要求提供，以便于安全操作。

A material safety data sheet for the safe handling of this product is available on request.

储存 常温储存。液体可能会受潮气影响，包装应随时保持密封状态。

Storage Storage at room temperature is recommended. Liquid products may be affected by moisture and containers should be kept tightly closed.